

Sugar Syrup Filter Press

The Sugar Syrup Filter Press is used to remove all dust and particles that are found in sugar when it is made a syrup. It is fabricated fully from SS 304. It has a capacity to filter about 500 liters per hour. It has a 1 Hp motor and SS pump. The filter section has 7 special filter pads through which the sugar syrup passes and is completely filtered.

The filter tank is fitted with a pressure gage, safety release and air release valve. The filter pads have to be cleaned each time they are used. However, they have to be changed periodically depending on their usage. The filter tank and its connecting pipes can be dismantled and cleaned in a short time. The filter press assembly is mounted on wheels for portability.



Showroom & Demo Center

2 & 3, Rajagopal Layout, Avarampalayam Road,
Peelamedu, Coimbatore - 641 004. Tamil Nadu, India.
Ph: 0422 - 2563470 Mob: 7397395652

City Showroom

194 - A, Ranga Konar Street, Kattoor,
Coimbatore - 641 009. Tamil Nadu, india.
Ph: 0422 - 2233257

Factory

1/11, Venkataswamy Naidu Industrial Estate, Bharathi Colony, Peelamedu, Coimbatore - 641 004. Tamil Nadu, India.
Ph: 0422 - 2563450 / 2563480 / 2563191 Mob: 99525 66600 / 98422 56525